

## Ventilation Duct Fabric - Haining Comax New Material Co., Ltd.

### PVC Ventilation Duct Tarpaulin – PVC Tarpaulin Ventilation Duct Fabric 1500D\*2000D

9\*9 550gsm



#### Features

- ◆ Anti-Static performance; Matt/Glossy Finish available
- ◆ A variety of color choices are available
- ◆ Excellent tensile strength, tear resistance, extremely soft hand feeling
- ◆ Waterproof, flame retardant, Anti-UV, Anti-Bacterial, Anti-Mildew, Oil resistant; Strong and durable, not easy to wear
- ◆ Can be sewn or high frequency welded

#### Technical Data Sheet

Item Code	SVTVDF152099550	Test Method	
Base Fabric	1500D*2000D 9*9	DIN EN ISO2060	
Weight (GSM)	550	DIN53352	
Tensile Strength	Warp (N/5cm)	2000	DIN53354
	Weft (N/5cm)	1800	DIN53354
Tear Strength	Warp (N/5cm)	200	DIN53363
	Weft (N/5cm)	180	DIN53363
Peeling Strength	Warp (N/5cm)	80	DIN53357
	Weft (N/5cm)	80	DIN53357
Temperature	-30°C/+70°C		

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,  
Haining, Zhejiang, China  
Tel: +86-573-80776996 Fax: +86-573-80776998  
Mob/Skype/Wechat/WhatsApp: +86-15858322153  
<mailto:supervinyltarp@163.com> <https://www.vinyltarpaulin.com/>

